

Flagship laser ODL-721

Laser-lit rear-projection video walls for 24/7 control rooms



Powered with the latest RGB laser technology, Barco's Flagship laser rear-projection video walls delivers unseen brightness levels and vibrant colors, while offering a very low total cost of ownership (TCO). With its 10th generation of rear-projection video walls, Barco again raises the bar for critical infrastructure markets visualization.

Providing 2x more brightness than mainstream LED-lit rear-projection video walls, the Flagship laser series take away all brightness issues of earlier video walls. Because the high luminance allows operating under daylight conditions, control rooms can finally light up - which improves operator working conditions! Adding vibrant colors to this mix, that make all nuances clearly distinguishable, you make sure nothing is wrongly interpreted and situational awareness is enhanced.

Over 11 years of uninterrupted 24/7 operations

With the Flagship laser for 24/7 control rooms series, Barco takes another giant leap forward in terms of reliability. With a lifetime of at least 100,000 hours in eco-mode, operators enjoy a staggering 11.5 years of uninterrupted 24/7 operations. Redundancy of all critical components (including power supply, inputs, and drivers) make sure nothing is left to chance when it comes to uptime. Unlike laser-phosphor technology used by competitors and in non-24/7 meeting rooms, Barco's Flagship laser display series doesn't need a rotating color wheel to operate. Since each color can be uniquely controlled and is not dependent on the segment of a color wheel, it provides color control like never before and eliminates color breakup.

Automatic calibration and alignment

The engine of Barco's Flagship laser for 24/7 control rooms is fully motorized. Installers and maintenance staff will never need to open up the individual modules to perfectly align the individual cubes of the video wall. Using a web interface, the video wall can be remotely aligned by a single technician - including keystone correction. This is far more efficient, more reliable, and less time consuming, saving up to 50% of alignment and adjustments efforts. Combined with the Sense X automatic calibration system, continuously measuring and adjusting brightness and color levels over the complete video wall, users are sure the complete canvas is perfectly balanced at any time.

BARCO

Visibly yours

Product specifications

Flagship laser ODL-721

Resolution	Full HD (1920 x 1080 pixels)					
Screen	Screen type	WV-FEL	NoGap	CSI	Engine lifetime (hrs)	Power usage
	Boost	800 cd/m ²	680 cd/m ²	550 cd/m ²	60,000	260 W
	Normal	620 cd/m ²	530 cd/m ²	430 cd/m ²	80,000	200 W
	Eco	310 cd/m ²	265 cd/m ²	215 cd/m ²	100,000	120 W
	Horizontal half gain viewing angle	38°	36°	36°	-	-
	Vertical half gain viewing angle	21°	33°	34°	-	-
On-screen contrast	1800:1					
Color	Up to 170% EBU color triangle					
Display technology	Rear projection DLP					
White point	Customized white points					
Brightness uniformity	Typ. >95% ANSI 9 Typ. >90% ANSI 13					
Screen gap	Dependant on screen type					
Color stability	Sense X automatic calibration					
Dimensions	<ul style="list-style-type: none"> • Diagonal: 70" (Approx.) • Width: 1,550 mm 61.02" • Height: 872 mm 34.33" • Depth: 622 mm 24.49" • Weight: Projection Module: < 63 kg 139 lbs • Weight: Support frame: < 39 kg 86 lbs 					
Light source	RGB lasers illumination (Lasers Class 2)					
Redundancy	Redundant laser banks with redundant power supply drivers, input signal & external power supply					
Light source lifetime	> 100,000hrs in eco mode > 80,000hrs in normal mode > 60,000hrs in boost mode					
Conditions for operation	10°C-40°C 50°F-104°F Up to 80% humidity (non-condensing)					
AC input voltage	100 – 240 VAC, 50-60Hz					
Power	120W (eco) 200W (normal) 260W (boost)					
Heat dissipation	390 BTU/h (eco) 680 BTU/h (typ) 860 BTU/h (max)					
Signal	Redundant Dual link DVI					
Pixel clock	330 MHz					
Input frequency	24 – 62 Hz & 92 - 120 Hz					
Genlock	49 – 61 Hz ; 92 - 120 Hz					
Minimum frame delay	1 frame in minimum frame delay < 2-3 frames in all other cases at full frame rate					
Signal processing	Loop through Free cropping, free scaling					
Direct ethernet access	Built in web server					
Graphical user interface	All settings and operational parameters					
Integration to third party equipment	WEB service API					
Warranty	2 years					

Last updated: 01 Jun 2016
 Technical specifications are subject to change without prior notice.
 Please check www.barco.com for the latest information.

BARCO

Visibly yours