UNB

Ultra Narrow Bezel

OLMU-5520 / 5550

Seam Gap 5.7mm → **3.8mm**

The OLMU-5520/5550 advances new level of LED video wall standard with Ultra Narrow impact of 3.5mm seam line. This professional grade large scale format display designed for rugged 24/7 operation overwhelms your imagination by deploying in video wall of 10 x 10 configuration for various venue of installations

Brighter panel takes attractive impact to commercial display whereas lower bright panel delivers cost effective ownership for control or surveillance system

* Specification

Product Name		55" Multi-LCD Monitor	
Model Name		OLMU-5520	OLMU-5550
LCD Module	Brightness (Typ.)	500 cd / m^2	700 cd / m^2
	Contrast Ratio (Typ.)	1,400 : 1	1,400 : 1
	Bezel (R/L/U/D mm)	1.25/2.35/2.35/1.25 (3.5mm)	1.25/2.35/2.35/1.25 (3.5mm)
	Display Colors	1.07 Billion(10Bit)	1.07 Billion(10Bit)
	Lamp Life Time	Min. 40,000Hrs	Min. 40,000Hrs
AC Input Voltage		AC100V ~ 240V±10% (50/60Hz)	AC100V ~ 240V±10% (50/60Hz)
Power Consumption	Max	200W	270W
	Typical	115W	150W
	Stand-By	≤ 0.47W	≤ 0.47W
Surface Treatment		Haze 10%, Anti-glare Hard-Coating (3H)	Haze 44%, Anti-glare Hard-Coating (3H)
Input Video Signal	PC/DVI/HDMI Signal	VGA, SVGA, XGA, SXGA, UXGA, WXGA, 480p,576p, 720p(50/60),1080i(50/60),1080p(50/60)	
	HDCP	O	O
	Video Signal	X	X
	Frequency	H : 31.5 ~ 75kHz, V : 50 , 60 Hz	
In/Output Video Terminal	DVI	1/1	1/1
	PC	1/0	1/0
	HDMI	2/0	2/0
	DP	1/0	1/0
Control	RS-232	1/1	1/1
	LAN	O	O
	Remote Controll	O	O
	Key-Pad	O	O