

MLCD Video Wall



Ultra Thin Bezel Multi LCD. Breathtaking technology with Full HD and Ultra Narrow Bezel (5.5mm), the OLM-5501 will pioneer the multi display market with seamless tiled display experience and vivid image. Being equipped with eco-friendly LED BLU, the 55" FHD multi display consumes less power than conventional CCFL BLU model.



Special Features

Multivision	Yes (Daisy chain)
Bezel (Seam Gap)	5.5 mm
Max Multivision Layer (W x H)	10 x 10 (15x15 Option)
Built in temperature sensor	Yes
Built in light sensor	Option
OSD Languages	English / Korean / Japanese / Spanish / Italian / German / French / Russian / Chinese



◉ **Narrow → 46" Super Narrow → 55" Ultra Super Narrow**



◉ **Specification**

Item	Model	OLM-5501
DID Panel	DID Panel Inch	55"
	Number of Pixels	1920 x 1080 (WXGA)
	Brightness	700cd/m ²
	Contrast Ratio	3000:1
	Viewing Angle (H/W)	178° / 178°
	Life time	50,000 h
	Wall frame	Slide Bracket
Industrial AD Board	Input Ports	DVI-D / PC(D-Sub) / Component / CVBS / Audio / RS-232C , S-Video (Option)
	Output Ports	DVI-D / PC(D-Sub) / Component / CVBS / RS-232C , S-Video (Option)
	Amp	Built in 7W x 2 amp
	Digital Input Signal	SVGA / WVGA / XGA / SXGA / UXGA / WUXGA
	PC Input Signal	SVGA / WVGA / XGA / SXGA / UXGA / WUXGA
	Component Input Signal	480i / 480p / 576i / 576p / 720p / 1080i / 1080p
	CVBS Input Signal	NTSC / PAL / SECAM
Power	Baud Rate	9600
	Input Voltage	100 ~ 240V AC, 50/60hz
	Power Consumption	250W
	Stand By Power Consumption	< 1W

