

OLS-8401NLG		spec		Remarks
LCD Module	Panel Size	1,904 x 1,096 x 24mm (84inch diagonal)		
	Brightness	350 cd/m²		
	Life Time	30,000 (Min)		
	Resolution	3,840 x 2,160 (4K x 2K)		
	Back Light Unit	LED		
General	Weight	73Kg		
	dimension	1917 X 1103 X 95mm		
	Power Consumption	500W (max)		
		< 0.8W		
Video & control I/O	Video Input	HDMI 1.3 x 8 port (With HDCP) Or 2 UD input	HDMI	Resolution -1080p, UXGA / port 1080p, 1080i, 720p, 576p, 480p -UD / CH(per 4 HDMI port)
	Control	1 Serial comm. (RS232)	9pin D-sub	-Baud Rate : 9600 / 14400 / 19200 / 38400 / 57600 / 115200
		1 LAN (Ethernet)	RJ45	TCP / SNMP / HTTP
		1 USB (service port)	USB	F/W upgrade port
		OSD / Key button / IR		
function	Picture	Brightness , Contrast , (Color , Tint , Sharpness) Color Temp. mode, reset		
	screen	V/H-Position, Video Mute, Aspect ratio, reset		
	Setup A	Power saving ON/Off, baud rate, LAN IP, OSD, key lock, display & F/W version, reset		
	Setup B	information, reset		