

TransForm NGX-200

Compact X.11 display controller driving up to 8 HD displays



Barco's TransForm NGX-200 display controller is a compact and silent X.11 video wall controller, perfectly suited for driving small video walls or personal operator displays.

Based on Linux OS and native X-Server technology, the design of the system consequently excludes any incompatibility or performance issues of emulation systems, and makes the system a perfect display controller for all types of X.11 clients and applications.

Mature and hassle-free, with unique X.11 extensions

On top of the standard X.11 functionality the system excels with functional extensions like Barco's unique Multi Cursor extension XMC for supporting multiple operators on a single wall, and IP stream decoding for displaying streaming IP videos (h.264, mpeg4, mpeg2) and network-streamed desktop content using Barco's ProServer functionality on the video wall. The mature architecture of the system ensures hassle-free installation and 24/7 operation.

Features:

- Native X-Server technology
- Transparent, unrestricted use of the entire video wall for X-applications
- Barco-unique Multicursor Extension
- Up to 8 HD outputs through Barco's OverView OL, OVL video walls
- Universal IP streaming video decoding
- Intel (R) Core (TM) i5 quad core processor for concurrent application processing and software based media decoding
- Mature technology
- Compact form factor
- Low-noise operation
- Easy to set-up and operate

BARCO

Visibly yours

Product specifications

TransForm NGX-200

Platforms	NGP-200	
OS	Linux	
Software	Native X11R7 Server	
CPU	Intel Core i5 Quad Core Processor	
CPU frequency	3.0 GHz (up to 3.7GHz)	
Memory	4 GB RAM	
Hard disk	60 GB Solid-State Disk SSD	
Network	2x 1Gb/s LAN	
Graphics card	1x high-performance NVidia Quadro-series cards with 2x UHD DVI-DL outputs	
Output	Up to 2 UHD directly connected displays Up to 8 HD displays using Barco loop-through displays	
Input	Up to 24 Streaming video IP video sources H.264, MPEG-4, MPEG-2	
Performance	300 Vcores	
Form factor	3U ½ 19" Rackmount housing	
Power Supply	100-240V, 50/60Hz	
Dimensions	133mm x 220mm x 279mm 5.24" x 8.66" x 10.98"	
Weight	5.5 kg 12.13 lbs	
Temperature range	0°-40°C 32°-104°F	
Humidity	Max. 80% (non-condensing)	
Noise Level	Max. 31dbA (measured at 1m/32.8ft distance at 22°/72°F)	
Regulation Compliance	CE,CB, IEC 609501, ETL, CCC, BIS, FCC Class A	
Available models	Order No.	
	R9838202	NGX-200 display controller
Licensing	Order No.	
	R9805499	NGX.11 Display Controller Base License (mandatory, 1x per display controller)
	R9805598	NGX.11 XMC Multi Cursor License (optional, 1x per display controller)
	R9805705	NGX.11 IP Stream Decoding License (optional, 1x per source)
	R9805599	NGX.11 Output License (1x per display)