

Rigid-732

Extreme Rugged, Intel® P8400 Core™ 2 Duo, Fanless Embedded Controller



Features

- Wide Operating Temperature (-40 ~ 70°C)
- Fanless Design
- Wide Range DC power Input (10 ~ 28V)
- Rugged Design for Shock/Vibration Protection
- Rich Onboard I/O and Expansion Slots (2 x PCI, 1 x Mini-card)
- Support Various Video Interfaces (Analog RGB, DVI, DisplayPort, TV-out)
- Support Outside Accessible CF Slot
- Easy Installation/Maintenance
- Support DDR2 SO-DIMM up to 4GB



System

CPU	Intel® Core™ 2 Duo processor P8400 2.26GHz with 1066MHz FSB, 3M cache
Memory	2 x 200-pin Dual Channels DDR2 SO-DIMM Sockets up to 4GB at 667/800MHz (2GB WT DDR2-800 SDRAM installed by default)
Chipset	Intel® GM45 + ICH9M
Graphics	Intel® GM45 integrated GMA X4500, support DirectX 10, Shader Model 4.0
ATA	2 x Serial ATA ports with 300MB/s HDD transfer rate
LAN Chipset	2 x Realtek RTL8111 Gigabit Ethernet controllers
Watchdog Timer	1~255 levels reset

I/O

Serial Port	1 x DB-44 female connector Support 4 x RS-232 ports (COM4 is RS-232/422/485 selectable)
USB Port	8 x USB 2.0 ports
LAN	2 x RJ-45 ports for Gigabit Ethernet
Video Port	1 x DB-15 female connector for Analog RGB 1 x DisplayPort
TV-out	1 x 6-pin mini-DIN connector supports S-Video directly output or Composite output via external cable
Selectable Port	Either of DVI or Digital I/O or LPT 1 x DVI-D female connector for Digital Video Output 1 x 16-bit digital I/O, 8 in/8 out SPP/EPP/ECP mode for LPT
Audio	Mic-in/Line-out (6W pre-amplified)
Expansion Bus	2 x PCI slots with riser card 1 x Mini-card slot

Environmental

Operating Temp.	-40 ~ 70°C (-40 ~ 158°F), ambient w/ air flow
Storage Temp.	-40 ~ 85°C (-40 ~ 185°F)
Relative Humidity	10 ~ 95% @ 40°C (non-condensing)
Vibration	3 Grms/5~500Hz/random operation
Shock & Crash	Operating 20G (11ms), Non-operating 40G with HDD Operating 40G (11ms), Non-operating 60G with CF/SSD Crash 80G (11ms)

Qualification

Certification CE, FCC

Power Requirement

Power Input	DC 10~28V input (w/ 4-pin DC input terminal block with remote power on/off switch)
Power Consumption	60W (Max.)
Power Adapter	120W AC/DC adapter


Storage

Type	1 x 2.5" drive bay for HDD/SSD 1 x CompactFlash Type II Socket which can be outside accessible
-------------	---

Mechanical

Construction	Aluminum alloy
Mounting	Wall-mount (Default integrated)/Din rail mounting
Weight	4.2 kg (9.24 lb)
Dimensions (W x D x H)	195 x 268 x 100 mm (7.68" x 10.55" x 3.93")

Drawing



Ordering Information

Rigid-732	Fanless embedded controller
DRK-001	Din rail mounting kit
SSD-25080	Intel® 2.5" 80GB SATAII SSD kit