# **TF-20 II**

# Outdoor 20mm LED tile for fixed installation



## **Key features**

- 6,600 nits brightness
- 4,000:1 contrast ratio
- 16-bit color processing
- 8-bit dimming
- 8° downward LED configuration
- Low power consumption
- Designed for remote management
- Designed for 24/7 operation
- Wide operating temperature
- Low weight
- First green modular LED tile on the market



Barco's TF-20 II is a reliable LED tile that will cast powerful imagery in the best possible light. It offers 24/7 reliability at a competitive cost of ownership. With less power consumption and a lighter weight than similar products, Barco's TF-20 II is a perfect fit for digital signage and sports applications.

The TF-20 II's optimizations include environmentally friendly technologies that reduce light pollution, such as contrast-enhancing shaders that allow for lower brightness and lower power consumption as well as a higher visual performance and 8° downward angle on its LEDs. This ensures that light is targeted at your audience and less excess light is spilled, which leads to a lower power consumption and longer lifetime. This makes the TF-20 the first real green LED product in the market.




# **TF-20 II specifications**


|                                    | TF-20 II                                    |
|------------------------------------|---|
| Pixel pitch                        | 20 mm                                       |
| Typical brightness (calibrated)    | 6,600 nits <sup>1</sup>                     |
| LED configuration                  | 1R, 1G, 1B, tilted 8° downwards             |
| LED density                        | 7,513/m²                                    |
| Horizontal viewing angle           | -70°/+70° color shift                       |
| Vertical viewing angle             | -44°/+11° color shift                       |
| Typical power consumption          | 139 W/m²                                    |
| Typical heat dissipation           | 474 BTU/hr                                  |
| Color processing                   | 16-bit/color                                |
| Operating temperature <sup>2</sup> | -20° C to 45° C (-4° F to 113° F)           |
| Operating humidity                 | 10 to 99%                                   |
| Weight/tile                        | 38 kg (83.77 lbs)                           |
| Dimensions (HxMxD)                 | 960 x 960 x 230 mm (37.8 x 37.8 x 9.1 inch) |

Front or Back

CE/ETL/RohS, FCC Class A

IP65/IP54





Serviceability

Certification

Ruggedness (front/back)

### Belgium

Kennedypark 35 8500 Kortrijk Tel: +32 56 36 80 47 Fax: +32 56 36 83 86 sales.media@barco.com

#### **United States** 11101 Trade Center Drive Rancho Cordova, CA 95670

Tel: +1 888 414-7226 Fax: +1 916 859-2515 salesusa@barco.com

#### Asia Pacific

No. 16 Changsheng Road Changping Dist., Beijing, PRC,102200 Tel: +86 10 8010 1166 Fax: +86 10 8970 9812 marketing.media@barco.com

While the information and data given are

typical for the equipment described, product

specifications are subject to change without

M00336-R00-0210-DS

<sup>&</sup>lt;sup>(1)</sup> On LED axis

<sup>&</sup>lt;sup>(2)</sup> Ambient temperature