

MULTIMEDIA DATA/VIDEO PROJECTORS

Classrooms Will Never be the Same Again

Revolutionary thin-client projector with ultrashort-throw lens




New 

WD390U-EST

Amazingly Easy to Use Anytime, Anywhere...

Introducing the latest model of ultrashort-throw lens mobile projectors in the Mitsubishi Electric line-up, the WD390U-EST. Boasting bright 3000lm illumination and capable of projecting an 80-inch image at a distance of only 64cm (25inch) from the screen, this revolutionary projector reproduces clear, large-screen images even in the tightest of spaces. Connecting to a cloud computing service using the WD390U-EST as a thin client terminal allows users to log-in to a computer or server from the classroom. This eliminates the need to carry around data and enables simple, no-fuss projection. Used with a tablet incorporating the SidePad function or Wifi Doc, it is possible to expand the breadth of classroom communications even further. Mitsubishi Electric is helping to realize maximum potential by responding to users' needs.




Reasons for Adopting a Direct-throw Projector

As the name suggests, direct-throw projectors project images directly onto the screen, providing a better sense of focus than models that use mirror projection systems. Additionally, they do not need to be installed and are easy to carry around. Furthermore, a projection distance equivalent to that of mirror projection units has been realized.




The Definitive Mitsubishi Electric Thin Client Projector

When connected to a LAN, users can log-in to remote computers directly from the projector, retrieve stored images and play them back. Through the introduction of the LAN Display Function and Remote Log-in Function, use as a thin client is possible. As all operations can be performed through the LAN, it is easy to start up another projector at the time of changing classrooms. Faculty members no longer need to return to the staff room to change the log-in on the remote computer. The WD390U-EST itself also functions as a terminal adaptor, enabling connection to a cloud through a computer or server. Applications and data can be used in the cloud infrastructure environment, helping to reduce the amount invested in school equipment. A projector that is truly easy to use, the thin-client compatibility of the WD390U-EST provides enhanced convenience that makes giving presentations much easier.




Remote Log-in Function

Up until now, LAN Display System required that the projector be selected from a computer, so users had to go a computer whenever they wanted to use a projector. The WD390U-EST is equipped with a remote log-in function that enables users to log into a computer from the projector, eliminating the time and effort required to go to the computer to log in.



USB Display/LAN Display


To use the projector to reproduce images from a computer, a VGA cable, USB cable, LAN cable or commercially available wireless dongle can be used. For displaying images via a LAN, up to four computers can be connected to one projector. The projection screen can be divided into quarters, reproducing all computer screens simultaneously.



Notes:
1) For displaying images via a LAN, network settings are required.
2) Not all USB dongles are compatible.


Remote Desktop

When using the LAN Display function, a USB mouse or USB keyboard can be connected to the projector enabling direct access to a computer utilizing the Internet or other application.



Thin client Multi-user Server

If a server is installed at the school, different images to be projected simultaneously in each classroom.



PC requirement for thin client

- Server OS
 - Windows MultiPoint Server 2011
 - Windows Server 2008 R2
- Client OS
 - Windows XP Professional
 - Windows Vista (Ultimate, Business, Enterprise)
 - Windows 7 (Ultimate, Professional, Enterprise)




Expand Creativity and Learning Fun in the Classroom with Smartphones and Tablet Terminals

Download the free MirrorOp Receiver application and turn iPads, iPhones and Android phones/pads into tablet terminals.

SidePad Function

Used in combination with LAN Display System, the images being projected can be displayed on tablets or smartphones, and the computer can be operated from a tablet. Teachers can remotely access their computer when carrying a tablet with them in the classroom, thereby facilitating even closer communication with students during lessons.


* This feature can be used after downloading the MirrorOp Receiver application software (freeware).
The LAN Display System is included with the main unit.



Wifi Doc

Wifi Doc is application software that allows data stored on a tablet or smartphone (txt/pdf/ppt/xls/doc/jpeg files) to be sent directly to a projector and shown. Useful images can be quickly accessed and shared while simultaneously giving presenters the freedom to interact more closely with the audience.

- * Please download a freeware Wifi Doc application (both freeware and payware are available).
- * Mirroring of the tablet screen is not supported.
- * On tablets, it is not possible to edit files or send movies.
- * Movies and animations are not supported.
- * Communication fees incurred while downloading applications are to be paid for by the customer.




* MirrorOp, MirrorOp Receiver, and WiFi-Doc are registered trademarks, trademarks, or trade names of AWIND Inc.

Presentation


World Shortest* Focal Distance – 0.375 Throw Ratio/80in

*Units not equipped with mirrors
Note: Data researched by Mitsubishi Electric in March 2011.
Utilizing a large-diameter lens and optimal optical engine design, the shortest focal distance (throw ratio: 0.375) in the industry has been achieved. Even if the teacher or presenter must move in front of the projected image, they are neither blinded nor disturbed by projector light, enabling them to maintain eye contact with the audience at all times.



3000lm High Luminance

The high 3000lm luminance helps to ensure presentation images are clearly seen without lowering the light in the room.



3000:1 High Contrast

Dark chip3 is newly introduced to the DLP® chip line-up. Stray-light processing has been optimized for the optical system, achieving a high contrast of 3000:1. This makes it possible to reproduce sharp, vivid images in which sentences and other characters can be easily read.


3D READY – Enjoy the future today



User Friendly

Ultra Quiet 28dB Operation

Fan noise during projector operation can be distracting during a presentation or videoconference. The WD390U-EST operates at a significantly low noise level of only 28dB (i.e., in “low lamp” mode). As a result, presentations and conferences can be held without distracting projector noise in the background.




Top-loading lamp for easier maintenance




E-Zoom (Digital Zoom)

The E-Zoom function utilizes an electrical image-correction process to reduce the image size up to 30% (maximum reduction to 70% of original size). When zooming out, the focal point at the center of the image remains the same while the overall image dimensions are reduced. Clear, vivid images are reproduced even in small rooms where a long projection distance is not possible.



E-Shift

This function utilizes the electrical image-correction process to enable the user to adjust the position of the image projected up/down and left/right.* The adjustment range (up/down, left/right) is ±15% when the E-Zoom reduction ratio is 70% and ±10% when the reduction ratio is 80%.



Audio

Stand-by Audio/Audio Pass-through

When the projector is in stand-by mode, its 10W speaker can still be used. Additionally, while in stand-by mode, an external speaker can be used by connecting it via the Audio Out terminal.



Excellent Sound Projection (10W Speaker+Audio Mix)

A high-volume, 10W speaker is built-in, eliminating the need for an external speaker. Using the “Audio Mix” feature and wireless microphone sold separately, the presenter’s voice is reproduced loud and clear in real time.



Network

Simultaneous Message Display (Visual PA)

Simultaneous message display is a function included in LAN control operation (ProjectorView global+). Using a control room computer equipped with projector-control software, administrators can simultaneously send messages (up to 390 characters long) in real-time to projectors connected to the LAN. Ideal for broadcasting important information to multiple rooms in the school or building.

Network Connectivity


*The trademark of PjLink is trademark applied for registration or registered trademark in Japan, the United States, and other countries and areas.



Ecology

6000-hour Long-life Lamp (max. use set to Low mode)

A longer service life for the projection lamp has been achieved by incorporating an optimal design for lamp temperature control. Benefits include substantial reductions in projector operating cost and the labor required for changing the lamp.



Lamp life specification is an estimate based on verification under proper conditions and is not the duration of the warranty. Lamp will shut-off automatically when usage reaches the specified estimated maximum lamp hours. Service life may vary widely depending on usage and operating environment and conditions, as well as users’ adherence to the maintenance and cleaning procedures provided in the user manual.

Auto Power Off

If no image signal is output for a predetermined period of time*, power is automatically turned off, realizing energy savings by reducing needless power consumption.

Stand-by Wattage under 0.5W*

Stand-by (low) mode power consumption is less than 0.5W, offering increased energy savings and further contributing to environmental preservation.

Ultra Short-throw Projection

Brilliant Color™

Color Enhancer

Wall Screen

10W Speaker

USB/LAN Display

Remote Desktop

Stand-by Audio

Audio Mix

Computer-free Presentations

Visual PA

PjLink

Direct Power Off

Long-life Lamp

Low Stand-by Power

Top Loading Lamp

LAN (RJ-45)

HDMI

Closed Caption

Low Fan Noise

Picture Performance


Presentation

User-friendly

New WD390U-EST

WIDE WEGA


Input and Output Terminals



Specifications

Model	WD390U-EST
Display technology	0.65" 1-Chip DMD
Resolution	1280 × 800 (Total 1,024,000 pixels)
Brightness*	3000lm
Contrast ratio*	3000 : 1
Zoom/Focus	Digital Zoom (Zoom ratio 1.4:1) and Manual Focus
Picture size	70" – 180"
Throw ratio	0.375
Source lamp	Normal Mode: 230W (Shut Off Time: 3000hrs), Low Mode: 190W (Shut Off Time: 6000hrs)
PC compatibility	640 × 480 – 1280 × 800 – 1600 × 1200, 1080p Sync on Green available
Video compatibility	NTSC / NTSC 4.43 / PAL (including PAL-M, N) / SECAM / PAL-60 Component Video; 480i/p (525i/p), 576i/p (625i/p), 720p (750p), 1080i/p (1125i/p 60Hz), 1080i/p (1125i/p 50Hz)
Input terminals	RGB; mini D-sub 15pin × 2 Video; RCA × 1 + S-VIDEO × 1 Audio; Stereo mini jack (φ3.5mm) × 2 (one for PC1, another one for PC2) Digital; HDMI × 1 Video Audio; RCA jack (L/R) × 1
Output terminals	RGB; mini D-sub 15pin × 1 Audio; Stereo mini jack (φ3.5mm) × 1
Communication terminal	SERIAL; mini D-sub 9pin × 1 (RS232C) LAN (RJ-45); × 1 (Projector control, LAN Display) USB type-A; × 1 (Wireless USB Adapters, USB Flash Drive, Human Interface Device) USB type-B; × 1 (USB Display)
Audio speaker	10W Mono
Dimensions (W × H × D)	325 × 113 × 258 mm
Weight	4.1 kg (9.0 lbs)
Power requirements	AC 100-240V, 50/60Hz
Optional lamp	VLT-XD560LP

Screen Size and Projection Distance



The above numbers are approximate, and may be slightly different from the actual measurements.

Screen size chart

Screen (16 : 10)						Projection distance (L)				Height Projected Image (Hd)				Movable H Position at Longest (Tele) with E-Zoom/E-Shift				Movable V Position at Longest (Tele) with E-Zoom/E-Shift			
Diagonal size		Width		Height		Shortest (Wide)		Longest (Tele) with E-Zoom		Shortest (Wide)		Longest (Tele) with E-Zoom		Left	Right	Left	Right	Down	Up	Down	Up
inch	cm	inch	cm	inch	cm	inch	m	inch	m	inch	cm	inch	cm	inch	cm	inch	cm	inch	cm	inch	cm
70	178	59	151	37	94	22	0.56	31	0.79	4.6	12	12.2	31	-9 ← 0 → 9	-23 ← 0 → 23	-6 ← 0 → 6	-14 ← 0 → 14				
80	203	68	172	42	108	25	0.64	36	0.92	5.3	13	13.9	35	-10 ← 0 → 10	-26 ← 0 → 26	-6 ← 0 → 6	-16 ← 0 → 16				
100	254	85	215	53	135	32	0.82	46	1.17	6.6	17	17.4	44	-13 ← 0 → 13	-32 ← 0 → 32	-8 ← 0 → 8	-20 ← 0 → 20				
120	305	102	258	64	162	39	0.99	56	1.42	7.9	20	20.9	53	-15 ← 0 → 15	-39 ← 0 → 39	-10 ← 0 → 10	-24 ← 0 → 24				
150	381	127	323	79	202	49	1.25	–	–	9.9	25	–	–	– ← 0 → –	– ← 0 → –	– ← 0 → –	– ← 0 → –				
180	457	153	388	95	242	60	1.51	–	–	11.9	30	–	–	– ← 0 → –	– ← 0 → –	– ← 0 → –	– ← 0 → –				



for a greener tomorrow

Eco Changes is the Mitsubishi Electric Group's environmental statement, and expresses the Group's stance on environmental management. Through a wide range of businesses, we are helping contribute to the realization of a sustainable society.



MITSUBISHI ELECTRIC CORPORATION

HEAD OFFICE : TOKYO BLDG., 2-7-3, MARUNOUCHI, CHIYODA-KU, TOKYO 100-8310, JAPAN

MITSUBISHI ELECTRIC EUROPE (BENELUX Office)

Nijverheidsweg 23A, 3641 RP Mijdrecht - The Netherlands
Tel: +31 (0)297-282461 Fax: +31 (0)297-283936 - www.MitsubishiElectric.nl