

» KIM 986LCD/mITX «



Wallmount/Table Top

- » Intel® Core™2 Duo support
- » 1x PCI Slot free
- » Dual DVI
- » 4x RS 232
- » Dual CF Slot internal

HKTM 986(CD mITX# 04292009BC All data is for information purposes only and not guaranteed for legal purposes. Subject to change without notice. Information in this datasheet has been carefully checked and is All data is for information purposes only and not guaranteed for legal purposes. Subject to change a trademarks or registered trademarks of their respective owners. Believed to be accurate, however, no responsibility is assumed for inaccuranties. All band or product names are trademarks or registered trademarks of their respective owners.

KIM 986LCD/mITX

Kontron Intelligent Minicomputer

Kontron's KIM wall mount/Table Top Box PCs can be used for various applications as Medical, Gaming, Process Control, and in Embedded Applications.

The KIM Box PC is specifically designed for use within harsh and industrial environments. Supporting Processors up to Core 2 Duo KIM boosts the limits of performance. High speed Graphics enables performance. High speed Graphics enables precise 3 D pictures and brilliant view.

Due to the hughe amount of on board I/Os like 3x LAN, 6 * USB, 4 * COM KIM enables connectivity for most of all applications. Long term availablility, easy maintenance and serviceability protect your investment.

Based on Kontrons Mini ITX-Board, KIM offers flexible and scalable Configurations

System	KIM 986 LCD/mITX
Product Line	KIM
Dimension (H x W x D)	153 mm x 214 mm x 196 mm (6,02" x 8,42" x 7,72")
Weight	Approx. 4 kg
Interfaces Front	4 x RS232, PS/2 Mouse + Keyboard, 2 x LAN 10/100/1000, 1 x Firewire, 6 x USB 2.0, VGA
Controls on the frontside	ATX Switch
Internal drive bays	1 x 3,5" for SATA HDD, Dual CF adapter
Power supply	AC 110-240 VAC internal; optimal 24 VDC
Expansion slots	1 x PCI 32 bit 33 MHz half size
Memory	Up to 2 GB DDR2
Processor	Celeron 440 (1,86 GHz)
	T2500 (2 x 2,0 GHz)
	T7400 (2 x 2,16 GHz)
Temperature	
operating	0°C - 50°C
storage	-20°C to 70°C (-4°F to 149°F)
Humidity	
operating	5 to 95 % @ 40°C not condensing
storage	5 to 95 % @ 104°F not condensing
Shock	,
operating	5G 11ms duration, 6 directions (half-sine)
storage	15G 11ms duration, 6 directions (half-sine)
Vibration	
operating	10-500 Hz: 0,5G sine / 3 axis
storage	10-500 Hz: 1G sine / 3 axis
Approvals	CE, designed to meet UL
MTBF	~40.000 h



CORPORATE OFFICES

Europe, Middle East & Africa

Oskar-von-Miller-Str. 1 85386 Eching/Munich Germany

Tel.: +49 (0)8165/ 77 777
Fax: +49 (0)8165/ 77 279
info@kontron.com

North America

14118 Stowe Drive Poway, CA 92064-7147 USA

Tel.: +1 888 294 4558 Fax: +1 858 677 0898 info@us.kontron.com

Asia Pacific

17 Building, Block #1, ABP. 188 Southern West 4th Ring Road Beijing 100070, P.R.China

Tel.: + 86 10 63751188 Fax: + 86 10 83682438 info@kontron.cn

