

Aqeri
96247

Aqeri 96247 is a rugged 19" Cisco-based military switch for use in harsh environments. The chassis is fully sealed for protection against dust and corrosive elements. A fully aluminum construction stands for low radiation and high noise immunity. The rugged design gives protection against shocks and vibration. An internal heating and climate control system makes the unit usable in extremely low-temperature environments.

2U Ethernet Switch

Features:

- > Fully sealed aluminum 19" 2U chassis
- > Based on Cisco WS-2960-24TT-L switch board
- > 24 x 10/100 Mbit in 38999 MIL connectors
- Integrated heating and climate control with status port
- > 18-36 VDC







TECHNICAL SPECIFICATIONS:

Switchboard: Cisco WS-2960-24 TT-L

I/O Interfaces

10/100 Mbit: x24 **Console:** x1

CONNECTORS

10/100 Mbit: MIL-DTL-38999

Console: DSUB
DC in: MIL-C-5015

PHYSICAL CHARACTERISTICS

Dimensions: 444 x 88 x 400mm (WxHxD)

Weight: 8 kg

Color: Grey, other optional

ELECTRICAL SPECIFICATIONS

Power requirements: 18-36VDC operating (Safe start Min 21VDC, Max 33VDC)

Power consumption: 30W (excluding heaters)

ENVIRONMENTAL CHARACTERISTICS

Designed to fulfill

(Other standards on request): MIL-STD-461E

MIL-STD-1275B MIL-STD-810G European CE

Temperature Operating:-20 °C to +55 °CVibration Operating:10-500Hz, 1,04rmsShock Operating:15g, 11ms, ½ sine waveHumidity:5% to 95% non condensing

Altitude Operating: 3000m

We reserve the right to change the information of this document without further notice. 110314