

# UDX-4K22

21,000 lumens, 4K UHD, 3-chip DLP laser phosphor large venue projector



- **Stunning experiences thanks to high-brightness images**
- **Savings on installation and shipping time**
- **Laser phosphor light source for reduced costs**
- **24/7 operation**

The UDX range delivers stunning experiences and savings on installation and shipping time, reducing costs significantly. The most compact, high-brightness laser projectors with integrated cooling on the market bring reliable and razor-sharp 4K images to every type of event and venue.

The UDX-4K22 features 4K UHD resolution and 21,000 lumens light output to ensure flawless shows with accurate colors. The Constant Light Output (CLO) functionality also guarantees constant brightness and color over time. The UDX platform offers the widest color spectrum in the industry, matching the renowned Xenon quality and outperforming the Rec. 709 color space - without compromising on brightness.

### Cut costs with laser projection

Thanks to the laser phosphor light source, you can forget lamp-related costs, maintenance and image flicker. The UDX series delivers a long lifetime and high reliability to ensure minimum downtime. The compact and rugged design reduces shipping and labor costs. The modular components can be removed quickly to limit servicing time. You can also reuse your TLD+ lenses.

### Pick your brightness and resolution

The unique FLEX<sup>2</sup> feature allows you to tune and lock your brightness and resolution to a specific show so you can cover a wider range of brightness levels and resolutions with fewer projectors.

### Faster processing for sharper images

The Barco Pulse 4K electronics offer an intuitive interface and flexible, embedded control software. Its Single Step Processing (SSP) brings sharper images and less

latency.



**PRODUCT SPECIFICATIONS****UDX-4K22**

Projector type	4K UHD 3-chip DLP digital projector
Technology	0.9" DMD™ x3
Resolution	3,840 x 2,400 (4K UHD) / 2,560 x 1,600 (native)
Brightness	21,000 (WQ)/20,000 (4K UHD) center lumens*
Contrast ratio	2,000:1
Brightness uniformity	90%
Aspect ratio	16:10
ScenergiX	Horizontal and vertical edge blending
Lenses	TLD+ 0.37, 0.65-0.85, 0.8-1.16 ; 1.25-1.6:1 ; 1.5-2.0:1 ; 2.0-2.8:1 ; 2.8-4.5:1 ; 4.5-7.5:1 ; 7.5-11.5:1
Optical lens shift	Vert -100% to +130% / Hor +/-40% on zoom lenses memorized
Color correction	P7
Light source	Laser phosphor with inorganic phosphor wheel
Light source lifetime	+20,000 hrs
Optical dowser	Digital
Picture-in-picture	Two sources simultaneously
Sealed DLP™ core	Standard
Orientation	360°
DMX 512	standard*
WARP	Direct adjust OSD + toolset
Integrated web server	Yes
CLO (constant light output)	Standard
3D	Active eye wear (optional), passive circular (optional); 3 flash up to 200Hz*
Inputs	Single HDBaseT; HDMI 2.0 (HDCP 2.2); DP 1.2 (HDCP 1.3); Quad SDI/HDSDI/dual HDSDI/6G/BarcoLink
Optional Inputs	Quad DP1.2
Input resolutions	From NTSC up to 4K (4,096 x 2,160)
Max. pixel clock	600 Mhz
Software tools	Projector Toolset + Android* app + iOS* app
Control	XLR wired + IR, RS232, Wifi*, GSM* (opt)
Network connection	10/100 base-T, RJ-45 connection, Wifi* (optional)
Power requirements	120-160 V(reduced power) / 200-240 V (+/- 10%), 20 A, 50-60 Hz
Max. power consumption	1,900W @ 230 volts STBY
Noise level (typical at 25°C/77°F)	49dB(A)
Operational ambient temperature	0°-40°C/ 32°-104°F (45°C reduced power)
Operational humidity	0-80% (non condens)
Dissipation BTU	Max. 6,600 BTU/h
Dimensions (WxLxH)	660 x 830 x 350 mm (25.98 x 32.67 x 13.77")
Shipping Dimensions	(LxWxH)1,200 x 980 x 760 mm (47.24 x 38.58 x 29.92")
Weight	87.5 kg (193 lbs)/shipping weight from factory: 105kg (231lbs)
Standard accessories	Power cord, wireless/XLR wired rugged remote control

**PRODUCT SPECIFICATIONS****UDX-4K22**

Certifications	Compliant with UL60950-1 and EN60950-1, complies with FCC rules & regulations, part 15 Class A and CE EN55032 Class A, Rohs
Warranty	3 years
*	Software upgradeable. Check with your local authorized Barco sales representative for full details.

**Last updated: 02 Feb 2018**

Technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest information.