

TransForm NGX-210

Compact X.11 display controller driving up to 16 HD displays



- **Native X.11-Server technology**
- **Transparent , unrestricted use of the entire video wall for X.11-applications**
- **Barco-unique Multicursor Extension**
- **Up to 16 HD outputs in combination with Barco's video walls**

Barco's TransForm NGX-210 display controller is a compact and silent X.11 video wall controller, perfectly suited for driving small video walls or personal operator displays.

Based on Linux OS and native X-Server technology, the design of the system consequently excludes any incompatibility or performance issues of emulation systems, and makes the system a perfect display controller for all types of X.11 clients and applications.

Mature and hassle-free, with unique X.11 extensions

On top of the standard X.11 functionality the system excels with functional extensions like Barco's unique Multi Cursor extension XMC for supporting multiple operators on a single wall, and IP stream decoding for displaying streaming IP videos (h.264, mpeg4, mpeg2) and network-streamed desktop content using Barco's ProServer functionality on the video wall. The mature architecture of the system ensures hassle-free installation and 24/7 operation.

Features:

PRODUCT SPECIFICATIONS**TRANSFORM NGX-210**

Processor	Intel(R) Core(TM) i7 Quad core processor 3.2GHz (4.0GHz max. Turbo frequency)	
OS	Linux	
Software	Native X11R7 Server	
Memory	4 GB RAM	
Hard disk	128 GB Solid-State Disk SSD	
Network	2x 1Gb/s LAN	
Graphics card	1x high- performance NVidia Quadro -series cards with 4x DP1.2 outputs (DVI-D SingleLink/DualLink supported via included/optional Adapter)	
Output	Up to 4x 4k/UHD displays Up to 16x HD displays using Barco loop-through displays	
Input	Up to 24 Streaming video IP video sources H.264, MPEG-4, MPEG-2	
Power supply	100 --240V, 50/60Hz	
Power consumption	124W (typ) / 270W (max)	
Form factor	3U ½ 19" Rackmount housing	
Dimensions	133mm x 220mm x 300mm 5.24" x 8.66" x 11.81"	
Weight	5.5 kg 12.13 lbs	
Temperature range	0°-40°C 32°-104°F	
Humidity	Max. 80% (non-condensing)	
Noise Level	Max. 31dbA (measured at 1m/32.8ft distance at 22°/72°F)	
Regulation Compliance	CE,CB, IEC 609501, ETL, CCC, BIS, FCC Class A Regulatory model Id: NGP-210	
Available models	Order No.	
	R9821002	NGX-210 Display Controller
	R9821002I	NGX-210 Display Controller CN
	R9821002F	NGX-210 Display Controller EU
	R9821002G	NGX-210 Display Controller UK
	R9821002B	NGX-210 Display Controller US
	R9821002X	NGX-210 Display Controller XX
Licensing	Order No.	
	R9805499	NGX.11 Display Controller Base License (mandatory, 1x per display controller)
	R9805598	NGX.11 XMC Multi Cursor License (optional, 1x per display controller)
	R9805705	NGX.11 IP Stream Decoding License (optional, 1x per source)
	R9805599	NGX.11 Output License (1x per display)

Last updated: 07 Feb 2018Technical specifications are subject to change without prior notice. Please check www.barco.com for the latest information.