

# HOMELAND SECURITY MILITARY C3I COMMAND CENTER



VISUALIZATION SYSTEMS

# **DISPLAY WALL SERIES**

# 2 x 3 x 46" **DEPLOYABLE LCD DISPLAY WALL**



105"

### **Key Features**

105" screen of 12 mega pixels

10' fast, easy and secure assembling

Ready to use in 30'

Transportable in weatherproof cases

Can be installed on uneven ground up to 5% incline

Temporary indoor and field installations

Patented system

Emission security TEMPEST standards:

- ▶ NATO SDIP-27 Level A
- USA NSTISSAM Level 1

### TRANSPORTABLE INFORMATION OVERVIEW SYSTEM

Today's critical field operations rely on visualization to monitor and make tactical decisions IRTS 2 x 3 deployable LCD display wall is a COTS field-proven system for worldwide Army forces requirements and is used by French Armed Forces. Mobile and transportable anywhere it produces reliable picture in any location, whether it is a temporary installation in a building, in a shelter or a soft-top cover - such as a field command post or an inflatable tent.

### Multiple feeds of information onto multiple displays

The 2 x 3 IRTS display wall is the ideal monitoring and decision-making support tool: Ergonomic and easy to assemble, it can be installed on uneven ground keeping though a consistent sound & image quality.

IRTS 46" monitors near-seamless 2 x 3 LCD display wall is an energy and cost efficient package.

With its specific features, IRTS Rugged 46" Thin Edge - R46TE - monitor is specifically designed for a deployable video wall.

IRTS is constantly striving to promote innovation and respond to market challenges, while maintaining its prices at a competitive level.

See also the IRTS' 2 x 2 and 3 x 3 LCD display walls and R46TE 46" LCD monitor.

WWW.IRTS-DISPLAYWALL.COM



# PRODUCT SPECIFICATIONS

		2 x 3 Mobile W	Vall				
Main Features 46" monitor							
	Diagonal Size	105"	Dot p		0.53025 mm (H), 0.53025 mm (V)		
Display area	Dimensions	2036 (H) x 1717 (V) mm		ing angles	178° (H) / 178° (V)		
	Resolution	3840 x 3240	Response time		8 ms		
	Screen ratio	6:5	Contrast ratio		3500 : 1		
	Brightness	450 CQ/M²	450 cd/m <sup>2</sup>				
Display wall controller	Video outputs	1 x Full HD (1920 x 1080) DVI local display port					
		10 x DVI Full HD (1920 x 1080) display ports					
	Video inputs	1 x composite					
		1 x 60 W equalizer 1 x microphone					
Audio	1 x anti-larsen box 2 x speakers						
	1 x RCA inputs						
Dedicated workstation		6 x Full HD	(1920 x 1080)	video display	outputs		
Software	Wall Control Red (Datapath)						
Suitware	ACM (Samsung) Advanced Color Management						
Operating system		Windows 7 secured conf	figuration 2011-	-094684/DGA	MI/DT/SSI/IPS/AI/NC		
Electrical features	230 V, 1400 W max consumption						
Operatio	nal configuration						
6 x IRTS R46TE 46" monitors			1 x sound equi	pment (60 W-	amplifier equalizer + microphone + speakers)		
1 x monitors' lifting mechanism	m support frame 1 x UPS						
	keyboard + mouse + soft keyboard 1 x connecting cables bundle						
1 x dedicated workstation, 6 ac		ts outputs					
Structure							
Flevator	1 x mechanized support structure 4 x ground stabilizers (+ front protected)						
Liovator	Small foot print 1036 x 1460 mm						
Controls	·						
30	Adjustable						
Height	Min. height at top of display wall : 2517 mm						
	Max. height at top of display wall: 2970 mm						
Display v	Display wall controller DATAPATH VSN 970						
	2 x Image DP4: 6 x display port video output connectors						
Graphic cards	2 x Quadri Capture Vision HD4: 8 x DVI video input connectors						
	1 x Capture Vision HV-HD: 2 x DVI video outputs + composite video input connectors						
	2 x Western Digital RED 750						
Mother board connectors	Back: 2 x USB 3.0, 2 x USB 2.0, 1 x DVI-D, Front: 2 x USB 3.0						
Electrical features	230 V, 525 W consumption						
Physical features	445 x 410 x 182 mm, 22 kg, aluminum, black						
Operating system	Windows 7 Pro 64 OEM, Secure Computer System						
Options							
•	Up to 16 captures display wall controller configuration						
Configuration							
Brightness	1.0						
	700 cd/m² brightness, 24/7 operating monitor nental Conditions						
	Specific transport case						
Shocks	· ·						
Humidity							
Ingress Protection							
Operating temperature	+ 5° to + 35° C						
Storage temperature	- 20° to + 49° C						
Warranty	Warranty						
	Two-year limited warranty (parts and labor), factory return under RMA procedure.						
	Additional 2-year coverage and customized service plans available on request.						



IRTS

639 Boulevard des Armaris = 83100 Toulon = France

Tel.: +33 (0)4 94 20 78 00 • Fax : +33 (0)4 94 20 78 01 —

IRTS NATO CODE: FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com




### PATENTED ASSEMBLY PROCESS

Combined with its D-LED DID technology, its 1.8 mm edges and 5.5 mm bezel-to-bezel width, the R46TE monitor offers a wide and uniform picture. Display effectiveness is maximized, making any information perfectly readable to any attendance.

IRTS Rugged 46" Thin Edge - R46TE - monitor is specifically designed to be mounted in a video wall. The rear side of the monitor integrates three twist locks (A), two carrying handles (B), as well as written handling instructions to make assembling & disassembling safe and easy.







Monitors are secured together by means of locking hooks.



The 3 twist locks enable to lock the monitor into position or release it from the structure.

IRTS' patented shock absorbers protect the monitor from being damaged when assembling the wall.





A 90° rotation enables to stick the handles out, so 2 persons can carry the monitor.

В




### IRT

639 Boulevard des Armaris = 83100 Toulon = France Tel.: +33 (0)4 94 20 78 00 = Fax : +33 (0)4 94 20 78 01

IRTS NATO CODE : FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com

# VIDEO WALL SYSTEM DESCRIPTION



- (Larsen) equipment,
- Integrity of your data and equipment is ensured by an integrated UPS.
- > 2 x 3 LCD wall offers extended video display outputs via a dedicated workstation.

0000000

A computer connection enables to drive the controller through a KMV - keyboard, video (monitor) and mouse.

A programmable keyboard - soft keyboard - enables recovering any memorized scenario, and using it at the press of a key. Scenarios are based on a selection of 11 captures displayed on the wall that can be combined at will.

Every piece of data is transferred through cable connection, ensuring therefore full confidentiality - as opposed to wireless communication - of the transmission.



639 Boulevard des Armaris • 83100 Toulon • France Tel.: +33 (0)4 94 20 78 00 • Fax: +33 (0)4 94 20 78 01 -


IRTS NATO CODE: FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com

- RUGGED DISPLAYS & COMPUTERS



# PRODUCT DESIGN





### IRTS

639 Boulevard des Armaris = 83100 Toulon = France Tel.: +33 [0]4 94 20 78 00 = Fax : +33 [0]4 94 20 78 01 —


IRTS NATO CODE: FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com


# DIMENSIONS, HEIGHT ADJUSTMENT & SPACE REQUIREMENT





### Dimensions are in meters (m).













639 Boulevard des Armaris = 83100 Toulon = France Tel.: +33 (0)4 94 20 78 00 • Fax : +33 (0)4 94 20 78 01 -

IRTS NATO CODE: FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com



## MOBILITY / TRANSPORT

Transportable, the 46" monitors 2 x 3 wall can be installed by only two persons.

The 6 monitors, support frame, display wall controller, computer and accessories are carried in 9 specific cases, labeled for chronological order of assembly:

	Cases (9)				
	1 x Large case				
Dimensions	1161 x 479 x 954 mm	263 1/9			
Weight	< 100 Kg				
Contents	Support frame lifting mechanism	= 2/9	are the transfer		
	1 x Large case	<b>2.3 2.70 2.3 3.79</b>	#		
Dimensions	1161 x 479 x 954 mm				
Weight	< 100 kg				
Contents	Support frame lifting mechanism accessories	<b>34/9</b>	A HALL		
	3 x Large cases	55			
Dimensions	1161 x 479 x 954 mm each	<sub>2x3</sub> 5/9			
Weight	< 100 Kg each				
Contents	6 x 46" monitors				
	1 x 8U case	1			
Dimensions	750 x 702 x 572 mm				
Weight	80 kg	80 kg			
	Controller 6/9	<sub>253</sub> 6/9			
Contents	Secured back panel with silk printed identified connections				
	Rackmounted audio amplifier with 3 inputs				
	Rackmounted 1000 VA UPS				
	3 x Reinforced cases	7/9			
Dimensions	794 x 615 x 444 mm each	2x3			
Weight	< 50 kg each	8/9			
	1 x A/V accessories	23 9/9			
Contents	1 x Dedicated workstation - PC, monitor, keyboard, mouse				
	1 x Cables w/ wheels and handles	23 010			
	Total weight				
< 730 kg	< 1610 lb				
Total volume / surface area					
20-foot container	2500 (w) x 1900 (d) x 1000 (h) mm / 4.5 m² (49 ft²)				



### TRANSPORT CASES CONFIGURATION

Basic 2x3 configuration: 9 cases



ILS 2x3 configuration: 2 additional cases





639 Boulevard des Armaris • 83100 Toulon • France

Tel.: +33 (0)4 94 20 78 00 • Fax: +33 (0)4 94 20 78 01 -

IRTS NATO CODE: FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com

# 7

## WALL OF FAME



IRTS is proud to support the French armed forces in every theater of operations where they are involved to ensure national security and our safety as well as to participate in peacekeeping operations.







SICF







### IRTS

639 Boulevard des Armaris = 83100 Toulon = France Tel.: +33 [0]4 94 20 78 00 = Fax : +33 [0]4 94 20 78 01 —

IRTS NATO CODE: FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com