

DEFENSE & SECURITY C3I COMMAND CENTER DISASTER MANAGEMENT



VISUALIZATION SYSTEMS

DISPLAY WALL SERIES



2 x 2 x 55" **DEPLOYABLE LCD DISPLAY WALL**



110"



Key Features

110" screen, 4K

10' fast, easy and secure assembling

Ready to use in 30'

Transportable in weatherproof cases

Can be installed on uneven ground up to 5% incline

Temporary indoor and field installations

Patented system

TRANSPORTABLE INFORMATION OVERVIEW SYSTEM

Today's critical field operations rely on visualization to monitor and make tactical decisions IRTS 2 x 2 deployable LCD display wall is a COTS field-proven system for worldwide Army forces requirements and is used by French Armed Forces. Mobile and transportable anywhere it produces reliable picture in any location, whether it is a temporary installation in a building, in a shelter or a soft-top cover - such as a field command post or an inflatable tent.

Multiple feeds of information onto multiple displays

The 2 x 2 IRTS display wall is the ideal monitoring and decision-making support tool: Ergonomic and easy to assemble, it can be installed on uneven ground keeping though a consistent sound & image quality.

IRTS 55" monitors near-seamless 2 x 2 LCD display wall is an energy and cost efficient entry level package.

With its specific features, IRTS Rugged 55" Thin Edge - **R55TE** - **monitor** is specifically designed for a deployable video wall.

IRTS is constantly striving to promote innovation and respond to market challenges, while maintaining its prices at a competitive level.

See also the IRTS' 46 inches 2 x 2 (4 monitors), 2 x 3 (6 monitors) and 3 x 3 (9 monitors) LCD display walls as well as R46TE 46" & R55TE 55" LCD monitors.



PRODUCT SPECIFICATIONS

<u>. ' . '</u>		2 x 2 Mobile Wall				
Main Fea	atures			55" monitor		
	Diagonal size	110"	Dot pitch	0.63 mm (H), 0.63 mm (V)		
Display area	Dimensions	2428 (H) x 1300 (V) mm	Viewing angles	178° (H) / 178° (V)		
	Resolution	3840 x 2160 4K	Response time	8 ms (G to G)		
	Screen ratio	16:9	Contrast ratio	3500 : 1		
	Brightness	500 cd/m ²	Display color	8 bit - 16.7 M		
Display wall controller	Video outputs 4 x Full HD (1920 x 1080) display ports					
	viueo outputs	1 x Full HD (1920 x 1080) DVI local display port				
	Video inputs	10 x DVI Full HD (1920 x 1080) display ports				
	viuco inputo	1 x composite				
Audio	1 x 60 W equalizer 1 x microphone					
	1 x RCA inputs 2 x speakers					
	1 x anti-larsen box					
Virtual desktop converter	4 x Full HD (1920 x 1080) video display outputs					
0.0	Wall Control Red (Datapath)					
Software		ACM (Samsung) Advanced Color Manag	gement		
Operating system	Windows 7 secured configuration 2011-094684/DGA MI/DT/SSI/IPS/AI/NC					
Electrical features	230 V, 1200 W max consumption					
	nal configuration	250 V, 12	.00 W max consumption			
4 x IRTS R55TE 55" monitors	nar connyuration	1 v e	ound equipment (60 W-	amplifier equalizer + microphone + speakers)		
1 x monitors support frame lift	na machaniem	1x1		amplifier equalizer + microphone + speakers)		
1 x media server + 24" laptop +			onnecting cables bundle			
<u> </u>		PCle = 4 video display ports outputs	onnecting capies bundle	,		
Structure		ole – 4 video dispiay ports outputs				
on acture	1 x mechanized support	structure				
Elevator	4 x ground stabilizers (+ front protected)					
	Small foot print 1036 x 1460 mm					
Controls	Up & down button for e					
	Adjustable					
Height	Min. height at top of display wall: 1950 mm					
	Max. height at top of display wall: 2970 mm					
Display v	Display wall controller DATAPATH VSN 970					
·	1 x Image DP4: 4 x display port video output connectors					
Graphic cards	2 x Quadri Capture Vision HD4: 8 x DVI video input connectors					
	1 x Capture Vision HV-HD: 2 x DVI video outputs + composite video input connectors					
Hard drive	2 x Western Digital RED 750					
	Back: 2 x USB 3.0, 2 x USB 2.0, 1 x DVI-D, Front: 2 x USB 3.0					
Electrical features	230 V, 500 W consumption					
Physical features	445 x 410 x 182 mm, 22 kg, aluminum, black					
Operating system	Windows 7 Pro 64 OEM, Secure Computer System					
Options						
Controller	Up to 16 captures display wall controller configuration					
Configuration	Upgrade kit to 2x3 or 3x3 display wall					
Brightness	700 cd/m² brightness, 24/7 operating monitor					
	nental Conditions					
Vibrations						
Shocks	Specific transport case					
Humidity	30 to 80%					
Ingress Protection	IP50					
Operating temperature						
Storage temperature - 20° to + 49° C						
Warranty						
	Two-year limited warranty (parts and labor), factory return under RMA procedure.					
	Additional 2 years coverage and customized service plans available on request.					



IRTS

639 Boulevard des Armaris • 83100 Toulon • France

Tel.: +33 (0)4 94 20 78 00 • Fax: +33 (0)4 94 20 78 01 —

IRTS NATO CODE: FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com




PATENTED ASSEMBLY PROCESS

Combined with its D-LED DID technology, its 3.5 mm bezel-to-bezel width, the R55TE monitor offers a wide and uniform picture. Display effectiveness is maximized, making any information perfectly readable to any attendance.

IRTS Rugged 55" Thin Edge - R55TE - monitor is specifically designed to be mounted in a video wall. The rear side of the monitor integrates three twist locks (A) and two carrying handles (B) to make assembling & disassembling safe and easy.






Monitors are secured together by means of locking hooks.



The 3 twist locks enable to lock the monitor into position or release it from the structure.

IRTS' patented shock absorbers protect the monitor from being damaged when assembling the wall.





Two handles on each side

enable 2 persons to carry the monitor.




IRTS

639 Boulevard des Armaris = 83100 Toulon = France Tel.: +33 (0)4 94 20 78 00 = Fax : +33 (0)4 94 20 78 01 -

IRTS NATO CODE: FAAJ7


Contact : sales@irts.fr • www.irts-displaywall.com

VIDEO WALL SYSTEM DESCRIPTION



The LCD display wall package is a full audio-visual system. Its display controller case consists of :

- Display controller to enable audio and video cabling,
- Sound amplifier & speakers as well as anti-feedback -Larsen - equipment,
- Integrity of your data and equipment is ensured by an integrated UPS.



A programmable keyboard - soft keyboard - enables recovering any memorized scenario, and using it at the press of a key.

Scenarios are based on a selection of 11 captures displayed on the wall that can be combined at will. Every piece of data is transferred through cable connection, ensuring therefore full confidentiality - as opposed to wireless communication - of the transmission.




IRTS

639 Boulevard des Armaris = 83100 Toulon = France Tel.: +33 (0)4 94 20 78 00 = Fax : +33 (0)4 94 20 78 01 —

IRTS NATO CODE: FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com

PRODUCT DESIGN





639 Boulevard des Armaris = 83100 Toulon = France Tel.: +33 (0)4 94 20 78 00 = Fax : +33 (0)4 94 20 78 01 —


IRTS NATO CODE: FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com

DIMENSIONS, HEIGHT ADJUSTMENT & SPACE REQUIREMENT





Dimensions are in millimeters (mm).
















IRTS

639 Boulevard des Armaris = 83100 Toulon = France Tel.: +33 (0)4 94 20 78 00 = Fax : +33 (0)4 94 20 78 01 -

IRTS NATO CODE : FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com



MOBILITY / TRANSPORT

Transportable, the 55" monitors 2 x 2 wall can be installed by only two persons. The 4 monitors, support frame, display wall controller and accessories are carried in seven specific cases, labeled for chronological order of assembly:

	Cases (7)				
	1 x Large case	= 177			
Dimensions	1161 x 479 x 954 mm	222			
Weight	< 100 Kg	₂₂₂ 2/7			
Contents	Support frame lifting mechanism	= 2/7			
	4 x Large cases	3/7			
Dimensions	1161 x 479 x 954 mm each	2.2 4/7			
Weight	< 100 Kg each	- - - - - - - - - -			
Contents	1 x 55" monitor + accessories	2.2 5//			
	1 x 8U case				
Dimensions	750 x 702 x 572 mm				
Weight	80 kg				
	Controller	₂₂₂ 6/7			
Contents	Secured back panel with silk printed identified connections				
Contents	Rackmounted audio amplifier with 3 inputs				
	Rackmounted 1000 VA UPS				
	1 x Reinforced cases				
Dimensions	794 x 615 x 444 mm each		$(\Pi - \Pi - \Pi - \Pi)$		
Weight	< 50 kg	2x2 7/7	\/		
Contents	Accessories and cables				
	Total weight				
< 580 kg	< 1280 lb				
	Total volume / surface area				
20-foot container	2000 (w) x 1900 (d) x 1000 (h) mm / 3.8 m² (41 ft²)				



TRANSPORT CASES CONFIGURATION

Basic 2x2 configuration: 7 cases



ILS 2x2 configuration: 1 additional case





639 Boulevard des Armaris • 83100 Toulon • France

Tel.: +33 (0)4 94 20 78 00 • Fax: +33 (0)4 94 20 78 01 -

IRTS NATO CODE: FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com

WALL OF FAME





IRTS is proud to support the French armed forces in every theater of operations where they are involved to ensure national security and our safety as well as to participate in peacekeeping operations.







SICF







IRTS

639 Boulevard des Armaris = 83100 Toulon = France Tel.: +33 (0)4 94 20 78 00 = Fax : +33 (0)4 94 20 78 01 —

IRTS NATO CODE: FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com