

DEFENSE & SECURITY C3I COMMAND CENTER **DISASTER MANAGEMENT**




VISUALIZATION SYSTEMS

VIDEO WALL SERIES

Barco UniSee

2 x 2 x 55"

DEPLOYABLE VIDEO WALL SOLUTION







See also the IRTS' 46 inches 2 x 2 (4 monitors), 2 x 3 (6 monitors) and 3 x 3 (9 monitors) LCD display walls as well as our range of rugged stand alone rugged monitors (HD and 4K).

Key Features

- 110" screen, 4K
- 20-minute fast, easy and secure assembling
- Ready to use in 30 minutes
- Transportable in weatherproof rugged transit cases
- Can be installed on uneven ground up to 5% incline
- Ideal for temporary indoor, command post & field installations
- Lock out patented system
- Multiple video sources, scalable per application
- User friendly and self explanatory plug and play software



OVERVIEW

The IRTS quad 55 deployable LCD video wall is a COTS fieldproven system ideal for the military and first responders. Mobile and transportable, it can be reliably deployed anywhere to rapidly provide a command and control or situation awareness in a tactical environment. Widely used by Army forces in the field, it is also the solution of choice for managing any critical situations. It can be set in minutes in a building, under an inflatable tent or in a mobile shelter

MULTIPLE VIDEO FEEDS FOR MULTIPLE DISPLAYS

The guad 55 IRTS video wall is the ideal tool for monitoring and displaying multiple video and audio sources. Easy to assemble, it can be installed on uneven ground while maintaining picture and sound quality. The IRTS quad 55» near-seamless video wall is an energy and cost efficient package. Designed around 4x55in digital signage LCDs, and provided with an open architecture graphic controller with expansion slots, this complete solution is prepared for added capability and will grow with the need. Delivered as a complete package, it's a real turn key solution, that can be tailored to specific requests.



PRODUCT SPECIFICATIONS

Main Fe	atures			55" monitor		
—— maili i C	Diagonal size	110"	Power supply	external		
Display area	Dimensions	2428 x 1300 mm (95.6" x 51.2")	Viewing angles	178° (H) / 178° (V)		
	Resolution	3840 x 2160 4K	Response time	Barco Sense X		
	Bezel	~ 1 mm	Contrast ratio	4000 : 1		
	MTBF	100 000 hours	Weight	~ 20 Kg		
	Brightness	800 cd/m ²	Front screen	protected		
Graphic controller	Dilgillicaa	4 x Full HD (1920 x 1080) display po		protected		
	Video outputs	1 x Full HD (1920 x 1080) DVI for local display				
	Video inputs	10 x DVI Full HD (1920 x 1080) DVI or HDMI				
	(option available)	Optional 4K capture card				
Audio Software	1 x 60 W equalizer		1 x micropho	one		
	1 x RCA inputs	s 2 x speakers				
	Wall Control Red or Pro (Optional)					
Sullware	Barco Sense X calibration system					
Operating system	Windows 10 PRO secured configuration					
	230 V, 1200 W max glol	oal consumption				
-	nal configuration					
4 x IRTS R55TE 55" monitors						
1 x support frame lifting mech						
1 x server, 24" screen, keyboa		eyboard 1 x cor	nnecting cables bundle			
1 x customized keyboard with						
Structure		th ambadded lifting avetom				
Litting quotom compost	1 x support structure with embedded lifting system					
Litting system compact	4 x ground stabilizers (+ front protected)					
Occitoria	Foot print 1036 x 1460 mm (3.4 ft x 4.8 ft)					
Controls	Up & down button (lifting engine)					
	Adjustable					
Height	Min. height at top of video wall: 1958mm (77.1")					
Diamlani		eo wall: 3152mm (124.1")	U VON 070			
Display	wall controller		H VSN 970			
	1 x Image DP4: 4 x display port video output connectors					
Grapnic cards	3 x Quadri Capture Vision HD4: 8 x DVI video input connectors					
Hard drive	Optional 4K capture card					
	2 x Western Digital SSD 250Go Back: 2 x USB 3.0, 2 x USB 2.0, 1 x DVI-D, Front: 2 x USB 3.0					
	230 V, 500 W consumption					
	445 x 410 x 182 mm (17.5"x 16.1" x 7.2"), 22Kg (53 lbs), aluminum enclosure, black					
	Windows 10 Pro 64 0EM, Secure Computer System					
Options						
•	Expansion slots available: up to 80 video captures					
	Upgrade kit to 2x3 or 3x3 display wall					
	Can drive a second independent video wall from the same sources - cable or fiber interface					
	nental Conditions	pondoni video wan nom the same sou	יייייייייייייייייייייייייייייייייייייי			
	In specific transport case MIL STD 810 uneven road transportation - trucks					
Shocks	In specific transport case MIL STD 810					
Humidity	30 to 80% as per MIL STD 810					
Ingress Protection	IP50					

Operating temperature + 5° to + 35° C as per MIL STD 810

Storage temperature - 20° to + 49° C as per MIL STD 810

Warranty

Two-year limited warranty (parts and labor)

Additional 2 years coverage and customized service plans available on request.



639 Boulevard des Armaris • 83100 Toulon • France

Tel.: +33 (0)4 94 20 78 00 • Fax : +33 (0)4 94 20 78 01 -

IRTS NATO CODE: FAAJ7


Contact : sales@irts.fr • www.irts-displaywall.com





PATENTED ASSEMBLY PROCESS


Based on D-LED DID technology and providing a 3.5 mm bezel-to-bezel width, the 55in monitor offers a sharp and vivid picture. Making any information easily readable, the IRTS 55» Thin Edge - monitor is specifically designed to be mounted and integrated as a video wall. The rear side of the monitor embeds three twist locks (A) and two carrying handles (B) to make assembling & disassembling safe, quick and easy while reducing the gap between displays to the minimum.











Monitors are secured during integration by means of locking devices.



The 2 twist devices lock the monitor into position or release it from the structure.

IRTS' patented shock absorbers protect the monitor from being damaged when assembling the wall.





Two handles on each side enable 2 persons to carry the monitor.






IRTS

639 Boulevard des Armaris • 83100 Toulon • France Tel.: +33 (0)4 94 20 78 00 • Fax : +33 (0)4 94 20 78 01 -

IRTS NATO CODE: FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com

VIDEO WALL SYSTEM DESCRIPTION




THE LCD VIDEO WALL PACKAGE IS A COMPLETE AUDIO & VIDEO SYSTEM



The graphic controller case consists of :

- One graphic controller enabling audio and video
- One sound amplifier & speakers as well as anti-feedback - Larsen - equipment
- · One integrated UPS to protect data and equipment against voltage interruptions



A programmable keyboard - soft keyboard - will store and recover any previous scenario (*).

(*) A scenario includes the selection of the video captures to be displayed and combined on the wall at will. For the standard version, 11 video captures are available, and up to 80 if all capture options are implemented in the video wall controller.



639 Boulevard des Armaris • 83100 Toulon • France Tel.: +33 (0)4 94 20 78 00 • Fax: +33 (0)4 94 20 78 01 -IRTS NATO CODE: FAAJ7

- RUGGED ELECTRONICS, COMPUTERS & DISPLAYS

Contact : sales@irts.fr • www.irts-displaywall.com

~

PRODUCT DESIGN












IRTS

639 Boulevard des Armaris = 83100 Toulon = France Tel.: +33 (0)4 94 20 78 00 = Fax : +33 (0)4 94 20 78 01 —


IRTS NATO CODE : FAAJ7


Contact : sales@irts.fr • www.irts-displaywall.com


HEIGHT ADJUSTMENT & SPACE REQUIREMENT













IRTS

639 Boulevard des Armaris = 83100 Toulon = France Tel.: +33 (0)4 94 20 78 00 = Fax : +33 (0)4 94 20 78 01 -

IRTS NATO CODE : FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com



MOBILITY / TRANSPORT

The quad-55 video wall can be installed by two persons only. The 4 monitors, support frame, video wall controller and accessories are stored and transported into eight specific cases, labeled for chronological order of assembly:

Cases (8)							
	1 x Large case						
Dimensions	1161 x 479 x 954 mm (45.7"x18.9"x37.6')	1/6					
Weight	< 100 Kg (< 220 lbs)						
Contents	Support frame lifting mechanism	2/6					
3 x Large cases		3/6					
Dimensions	1161 x 479 x 954 mm each (45.7"x18.9"x37.6')						
Weight	< 100 Kg each (< 220 lbs)	2x2 4/6					
Contents	2 x 55" monitor + câbles						
	1 x 8U case						
Dimensions	750 x 702 x 572 mm (29.5"x27.6"x22.5")						
Weight	80 Kg (< 200 lbs)	5/6					
	Controller						
Contents	Secured back panel with silk printed identified connections						
Contents	Rackmounted audio amplifier with 3 inputs						
	Rackmounted 1000 VA UPS						
	1 x Reinforced cases	2x2 6/6					
Dimensions	794 x 615 x 444 mm (31.2"x24.2"x 17.5")						
Weight	< 50 Kg (< 125 lbs)						
Contents	Accessories and cables	bles					
	Total weight						
	< 580 kg (< 1280 lbs)						
Total volume / surface area							
20-foot container	2000 (w) x 1900 (d) x 1000 (h) mm / 3.8 m ² 6.5 ft (w) x 6.2 ft (d) x 3.2 ft (h) / 41 sq ft						

TRANSPORT CASES CONFIGURATION Standard 2x2 display wall configuration: 8 cases







639 Boulevard des Armaris • 83100 Toulon • France Tel.: +33 (0)4 94 20 78 00 • Fax: +33 (0)4 94 20 78 01 -

IRTS NATO CODE: FAAJ7

Contact: sales@irts.fr • www.irts-displaywall.com

WALL OF FAME





IRTS is proud to support the French armed forces in every theater of operations, bringing solutions helping ensuring national security and enhancing our safety while participating in peacekeeping operations... »













639 Boulevard des Armaris = 83100 Toulon = France Tel.: +33 (0)4 94 20 78 00 • Fax : +33 (0)4 94 20 78 01 -

IRTS NATO CODE: FAAJ7

Contact : sales@irts.fr • www.irts-displaywall.com