## VBOX-3611-IP65

Intel Gen6 Core i7-6600U CPU with HD 520 GPU IP65 In-Vehicle Computer

## **Features**

- Intel Core i7-6600U
- Wireless Support LTE, WLAN, GPS, Bluetooth
- 9V 48V DC Power Input
- Smarter Vehicle Power Ignition for Variety Vehicle
- 4 x DI / 4 x DO with Relay 5V / 100mA
- IP65 Level for Water and Dust Proof











## Taiwan Patent No. M447854

| System              |   |
|---------------------|---|
| CPU                 | Intel Gen 6 Core i7-6600U 2.6GHz up to 3.4GHz   |
|                     | Intel Gen 6 Core i5-6300U 2.4GHz up to 3.0GHz   |
|                     | Intel Gen 6 Core i3-6100U 2.3GHz  |
|                     | Intel Gen 6 Dual Core 3955U 2.0GHz  |
| Memory              | 2 x DDR4 2133 MHz SO-DIMM up to 32GB  |
| LAN Chipset         | 1 x Intel I219LM (support iAMT for i5, i7 only) Gigabit Ethernet                              |
|                     | 1 x Intel I210-AT Gb/s Ethernet Controllers Onboard Support PXE and WOL                       |
| Audio               | Realtek ALC662 HD Codec Onboard   |
| Watchdog            | 1 ~ 255 Level Reset   |
| TPM                 | 2.0   |
| 1/0                 |   |
| Serial Port         | 2 x RS-232/422/485 (optional max. 4 x RS-232/422/485)   |
| USB Port            | 4 x USB 2.0 Ports on Front I/O  |
| LAN                 | 2 x M12 A-Code for GbE  |
| Video Port          | 1 x DVI-I*  |
| DIO Port            | 4 in and 4 out with Relay 5V / 100mA  |
| AIO Port            | 2 x Analog Input (0-48V)  |
| Audio               | 1 x Line-out, 1 x Mic-in and 1 x Line-in  |
|                     | (optional - 1 x Line-out additional)  |
| SIM Card Socket     | 2 x SIM Card Sockets Supported Onboard  |
|                     | *Use only with Single Link DVI Cables.  |
| Power Requirement   |   |
| Power Input         | 9V - 48V DC Power Input   |
| Power Protection    | Automatics Recovery Short Circuit Protection  |
| Power<br>Management | Vehicle Power Ignition for Variety Vehicle  |
| Battery(UPS)        | Internal Battery Kit for 10 Mins Operating (Optional)  Patent No.: M447854 - Build-in Battery |











Delay Time

Power Ignition

Wide Range

-----

| Storage                |  |  |
|------------------------|--|--|
| Туре                   | 1 x 2.5" Drive Bay for SATA Type Hard Disk Drive / SSD<br>1 x M.2 2280 co-layout 2242 M key SSD (SATA BUS) |  |
| Graphics               |  |  |
| Graphics               | Intel® HD Graphics 520   |  |
|                        | DirectX Video Acceleration (DXVA) for Accelerating Video   |  |
|                        | Processing - Full AVC/VC1/MPEG2 HW Decode  |  |
|                        | Supports DirectX 11/10.1/10/9 and OpenGL 4.0   |  |
| Resolution             | Up to 2560 x 1600 @85Hz  |  |
| Environmental          |  |  |
| Operating Temp.        | -40°C ~ 70°C, ambient w/ 0.6m/s airflow  |  |
| Storage Temp.          | -40°C ~ 80°C   |  |
| Relative Humidity      | 0% RH – 95% RH   |  |
| IP Rating              | IP65   |  |
| Vibration<br>(random)  | IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis with SSD   |  |
| Vibration<br>Operating | MIL-STD-810G, Method 514.6, Procedure I, Category 4  |  |
| Shock                  | Operating: MIL-STD-810G, Method 516.6, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD           |  |
| Certifications         | CE, FCC Class A, E-13  |  |
| Mechanical             |  |  |
| Construction           | Aluminum Alloy   |  |
| Mounting               | Supports Both of Wall-mount/VESA-mount   |  |
| Weight                 | 1980 g (Barebone)  |  |
| Dimensions             | 250 x 150 x 55 mm  |  |
| Ordering Information   |  |  |
| Part Number            | VBOX-3611-IP65   |  |
| Description            | Intel Gen6 Core i7-6600U CPU with HD 520 GPU IP65 In-Vehicle Computer                                      |  |
| State of Origin        | Made in Taiwan   |  |