

TL-248/2

19" Thin Lightweight display (1280 x 1024)



The TL-248/2 is ScioTeq's second-generation 19" thin and lightweight rugged display combining unmatched thinness with exceptionally low weight.

Next-generation technologies

ScioTeq's TL-248/2 offers a new generation upgrade solution for the TL-248. The updated model includes the latest innovations in electronics, inputs/outputs, video processing and touch technology.

The TL-248/2 features a first-class 19" SXGA LCD with LED backlight offering excellent performance in terms of brightness, crispness, dimming, contrast and viewing angle.

Several options and bezel configurations are available to address virtually any mounting need in any application. Additionally, the TL-248/2 combines this high level of performance and versatility with a very competitive price/performance value.

ScioTeq's TL displays have been designed for application in the most extreme environments, making them suited for naval combat, army, UAV and airborne applications.



Product specification				
Panel size		19"		
Resolution		1280x1024 (SXGA)		
Brightness		Typical 250 cd/m² (72,5 fL), LED backlight		
Contrast ratio		Typical 900:1		
		Standard	Rugged option	
Vibration	SHIPS	MIL-STD-167-1 Type 1	MIL-STD-167-1 Type 1	
	AIRBORN	2g MIL-E-5400T Fig.2, curve IIa (sheet 2 of 3)	2, curve IIa (sheet 2 of 3) 5g MIL-E-5400T Fig.2, curve IIIa (sheet 2 of 3)	
	RANDOM		MIL-STD-810F, Meth 514.5 Proc I, comp. wheeled vehicle (C2 & C3)	
Shock		MIL-STD-810F Meth 516.5 30g - 12,5ms	MIL-STD-810F, Meth 514.5 30g - 12,5ms	MIL-S-901D Lightweight Grade A
Operational temperature		Low temp: -10°C (immediate usable image at power up, image fully compliant with specs after 30 minutes) Low temp: 0°C High temp: 50°C	Low temp: -40°C High temp: +55°C	
Storage temperature		Low temp: -40°C High temp: +70°C	Low temp: -40°C High temp: +70°C	
Relative humidity		max. 95% @ 40°C	max. 95% @ 40°C	
Drip proof		MIL-STD-810F Meth 506.4 proc III	MIL-STD-810F Meth 506.4 proc III	
Altitude low pressure		40.000ft (187 mbar)	40.000ft (187 mbar)	
Rapid decompression			MIL-STD-810F, Meth 500.4 Proc III, 8.000ft to 40.000ft in 15s	
EMI / EMC		MIL-STD-461F - NAVY Applications	MIL-STD-461F - NAVY Applications / Navy fixed and Airforce Applications	
FCC		FCC-A	FCC-A	
Ingress protection		IPx5 on display front IPx5 on unit level with optional circular MIL connectors		
Signal inputs		2 x DVI, VGA, HD-SDI, RS-232 or RS-422, USB, Ethernet		
Power		28 VDC or 115-220VAC, per MIL-STD-704E and MIL-STD1275D guidelines		
Power consumption		45 W typical (without heating)		
Weight		± 10kg		
Options		LCD flicker compensation Touch screen Circular MIL connector interface		

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED

The information and data given are typical for the equipment described. However any individual item is subject to change without any notice.

SCI_TL-248_2-SpecSheet_190529

WWW.SCIOTEQ.COM

ScioTeq