

| CSE-200 General specifications | CSE-200+ General specifications |
|--|--|
| Operating system Windows 7/8/8.1/10 32 & 64 bit | Operating system Windows 7/8/8.1/10 32 & 64 bit |
| macOS 10.14/10.15 (Catalina) | macOS 10.14/10.15 (Catalina) |
| Android 9 & 10 (ClickShare app) | Android 9 & 10 (ClickShare app) |
| iOS 11, 12 & 13 (ClickShare app) | iOS 11, 12 & 13 (ClickShare app) |
| Video outputs 1x HDMI 1.2 | Video outputs 1x HDMI 1.4b |
| Output resolution 1920x1080 @60Hz | Video inputs 1x HDMI 1.2 |
| | Output resolution 4K UHD (3840*2160) @ 30Hz |
| Audio Via HDMI, analog via Audio Jack 3.5mm, S/PDIF | Input resolutions 1920x1080 @60Hz |
| AirPlay Support iOS 11, 12 & 13 / macOS 10.14, 10.15 | Audio Via HDMI, analog via Audio Jack 3.5mm, S/PDIF |
| Google Cast Support Android 9, 10 | AirPlay Support iOS 11, 12 & 13 / macOS 10.14, 10.15 |
| | Google Cast Support Android 9, 10 |
| Frame rate Up to 30fps* | Miracast support Miracast R2 support on Windows 10 |
| Number of sources simultaneous on screen 2 | Frame rate Up to 30fps* |
| Number of simultaneous connections 16 | Number of sources simultaneous on screen 2 |
| iPad, iPhone and Android compatibility Sharing of documents, browser, camera for both Android and iOS devices via ClickShare app or using AirPlay / Google Cast | Number of simultaneous connections 16 |
| Extended desktop Available for Windows, requires ClickShare Extension Pack. | iPad, iPhone and Android compatibility Sharing of documents, browser, camera for both Android and iOS devices via ClickShare app |
| Authentication protocol WPA2-PSK in stand-alone mode | Extended desktop Available for Windows, requires ClickShare Extension Pack. |
| WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode | Authentication protocol WPA2-PSK in stand-alone mode |
| Wireless transmission protocol IEEE 802.11 a/g/n | WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode |
| Reach Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit | Wireless transmission protocol IEEE 802.11 a/b/g/n/ac and IEEE 802.15.1 |
| Frequency band 2.4 GHZ and 5 GHz (DFS channels not supported) | Reach Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit |
| Connections 1x Ethernet LAN 100Mbit | Frequency band 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) |
| 2x (back) + 1x (front) USB | Connections 1x Ethernet LAN 1Gbit |
| Audio analog line out on mini jack socket (3.5mm), digital S/PDIF | 1x USB Type-C 2.0 (back); 2x USB Type A 2.0 (back); 1x USB Type A 2.0 (front) |
| Anti-theft system Kensington lock | Audio analog line out on mini jack socket (3.5mm), digital S/PDIF |
| Certifications FCC/CE | Anti-theft system Kensington lock |
| Warranty 3 years standard | Certifications FCC/CE |
| | Warranty 3 years standard |
| *In optimal WiFi conditions with minimal WiFi interference and as measured during our quality validation. Check Network Deployment Guide for more info on WiFi optimisation and ideal configuration depending on your network environment. | |
| | *In optimal WiFi conditions with minimal WiFi interference and as measured during our quality validation. Check Network Deployment Guide for more info on WiFi optimisation and ideal configuration depending on your network environment. |

| ClickShare Base Unit dimensions | ClickShare Base Unit dimensions |
|---|--|
| Dimensions (HxWxD) 205mm x 115mm x 45mm (excl. antennas) / 8.1" x 4.5" x 1.8" | Dimensions (HxWxD) 39mm x 200mm x 202mm |
| 205mm x 150mm x 135mm (incl. antennas) / 8.1" x 5.9" x 5.3" | |
| Power supply Standard 110/220 V AC plug or Power over Ethernet (PoE Plus) | Power supply Standard 110/220 V AC plug |
| Power consumption Operation: 6W (typical) / 18W (max) | Power consumption Operational: 50W (max) |
| Standby: 2.6W (ECO standby) / 0.4W (Deep standby) | Standby: <8W (networked standby), < 0.5W (deep standby mode) |
| Weight 600g / 1.32lbs | Weight 900 g |