

OLS Series

Model Name		OLS-8410NL	OLS-8420NL	OLS-8410T6L	OLS-8420T6L	OLS-7010NBG	OLS-7010T6B
Back Light Unit Type		LED				LED	
Resolution		3840 x 2160				1920 x 1080	
Active Display Area		1860.48 x 1045.52 mm				1549.44 x 871.56 mm	
Display Colors		16.7million colors (8bits)				16.7million colors (8bits)	
Brightness		350cd/m ²	500cd/m ²	350cd/m ²	500cd/m ²	400cd/m ²	
Contrast Ratio		1,600 : 1	1,400 : 1	1,600 : 1	1,400 : 1	4,000 : 1	
Lamp Life Time		50,000Hrs (Ta : 25±2℃)				50,000Hrs (Ta : 25±2℃)	
Power Consumption	Max	470 W				250 W	
	Typical	440 W				200 W	
	Stand-By	0.45 W				0.32 W	
Support Resolution		VGA, SVGA, XGA, SXGA, UXGA, WXGA, Quad HD/4K, 480p, 576p, 720p(50/60), 1080p(50/60)				VGA, SVGA, XGA, SXGA, UXGA, WXGA, 480p, 576p, 720p(50/60), 1080i(50/60), 1080p(50/60)	
In/Output Terminal		HDMI x 8, RS-232C x 1, LAN x 1, A/S x 1, IR x 1 USB x 1 (Touch model only)				DVI (In x 1, Out x 1), HDMI (In x 1), VGA (In x 1, Out x 1), Component (In x 1), S-Video (In x 1), AV (In x 2)	
	Audio	PC/DVI x 1, Component x 1, AV1 x 1, AV2/S-Video x 1					
Control Method		RS-232C, Ethernet, Remote Controller, Keypad					
Surface Treatment		Hard Coating (3H), Anti-Glare (Haze 10%)				Hard-Coating (2H), Anti-Glare (Haze 2.3%)	
Touch Function		-		6 Point IR Touch		-	6 Point IR Touch
Touch Glass		-		Anti-Glare / Normal		-	Anti-Glare / Normal
Dimension		1917 x 1103 x 95 mm		1977.2 x 1163.2 x 104.3 mm		1664.6 x 986.7 x 92.5 mm	1664.6 x 986.7 x 101.5 mm
Weight		72±0.5 kg		120±0.5 kg		53±1 kg	80±1 kg